

# RELAP5-3D two-phase behavior and predictions at low pressures

Diego Castelliti, Tewfik Hamidouche  
**SCK•CEN**

[diego.castelliti@sckcen.be](mailto:diego.castelliti@sckcen.be)



STUDIECENTRUM VOOR KERNENERGIE  
CENTRE D'ETUDE DE L'ENERGIE NUCLEAIRE

IRUG 2016 Meeting  
INL, Idaho Falls, 6-7 October 2016

- MYRRHA plant general description
- MYRRHA depressurization transient
- Experimental validation at low pressures
- Conclusions

# MYRRHA plant: purposes and general design


---

- MYRRHA: Multi-purpose hYbrid Research Reactor for High-tech Applications
- Pool-type Accelerator Driven System (ADS) with ability to operate also as critical reactor
- Liquid Lead-Bismuth Eutectic (LBE) as primary coolant
- Main purposes:
  - Flexible fast-spectrum irradiation facility
  - Minor Actinides (MAs) transmutation demonstrator
  - ADS demonstrator
  - GEN-IV European Technology Pilot Plant (ETPP) in the roadmap for Lead Fast Reactor (LFR)
- MYRRHA project recognized as high priority infrastructure for nuclear research in Europe

# MYRRHA plant: Primary Cooling System

- MYRRHA primary system design current status:




- Completely enclosed in primary vessel (pool-type)
- Design power: 110 MW
- Primary LBE:
  - Lower plenum (270 °C)
  - Upper plenum (~325 °C)
- Cold plenum separated from hot plenum by Diaphragm supporting core barrel and components' penetrations
- Above LBE free surface: Nitrogen layer



- Reactor vessel
- Reactor cover
- Diaphragm
- 4 Primary Heat Exchangers
- 2 Primary Pumps
- In-Vessel Fuel Handling Machine
- Core barrel
- Above Core Structure
- Core plug
- Spallation window

# MYRRHA plant: Fuel Assembly


- MOX fuel, 30% wt. Pu
- Fuel pin with wire spacer in 15-15Ti
- 127 pins per Fuel Assembly
- External wrapper



# MYRRHA plant: Sub-Critical Core Layout



- Sub-critical core:
  - 72 FAs
  - Maximum Power: 75 MW
  - $K_{eff} = 0.95 \rightarrow$  improved safety characteristics
  - 6 Control Rods
  - 6 In-Pile Section positions
  - No safety rods required
  - High and hard flux in core center  $\rightarrow$  MA transmutation

- 1 Spallation Target
- 72 FA
- 6 IPS
- 6 Abs. Devices
- 84 Dummy (LBE)
- 42 Reflector (Be)




# MYRRHA plant: Critical Core Layout

- Critical core:
  - 108 FAs
  - Maximum Power: 100 MW
  - 6 Control Rods
  - 3 Safety Rods
  - 4 In-Pile Section positions



# MYRRHA plant: Secondary and Tertiary Cooling System

- MYRRHA secondary system (one loop out of four) conceptual diagram:






# MYRRHA plant: Secondary and Tertiary Cooling System

---

- Secondary system:
  - Four independent secondary loops (linked through PHXs)
  - Operated with forced flow two-phase water mixture (16 bar, 200 °C)
  - Secondary water flow path:
    - PHX inlet (~saturated conditions)
    - PHX outlet ( $x \sim 0.3$ ,  $\alpha \sim 0.9$ )
    - Moisture separated in steam drum
  - In normal operation, secondary water temperature kept constant by control system (primary LBE temperature changing as a function of core loading)
- Tertiary system: dissipating heat to external environment through air condensers (forced circulation air fans)
- Condensed steam recirculated into steam drum

# MYRRHA plant: Decay Heat Removal

- Accidental conditions  
→ DHR in full natural circulation (primary, secondary and tertiary able to operate in passive mode)
- Two systems to remove decay heat power:
  - DHR-1: secondary and tertiary systems operating in passive mode
  - DHR-2: Reactor Vessel Auxiliary Cooling System



# MYRRHA safety analysis: FP projects participation


---

- Participation to several European FP projects in last decade:
  - FP6 IP-EUROTRANS, leading to finalization of MYRRHA/XT-ADS version of MYRRHA in June 2008
  - FP7 Central Design Team (CDT), defining MYRRHA/FASTEF version in March 2012
  - FP7 MAXSIMA (started in November 2012, ongoing), more focused on the MYRRHA safety analyses and component qualification
- European FP projects outcome partly used to define the latest version of MYRRHA design (currently in verification phase)
- Current version not definitive
  - MYRRHA design still evolving taking into account results from parallel R&D program


# MYRRHA safety analysis: RELAP5-3D model

Primary System

RELAP5 critical model v1.4



Core



Secondary +  
Tertiary Cooling  
System (x4)

Pumps + Primary  
Heat Exchangers

- RELAP5-3D MYRRHA plant model:
  - 2518 volumes, 2590 junctions
  - All cooling systems (primary, secondary, tertiary) simulated
  - Main control systems (Control Rods, secondary pressure) included

# MYRRHA safety analysis: Steady State

- First step: steady state analysis
  - Main steady state results reported:

Parameter	Unit	RELAP5-3D value	Design value
Lower plenum temperature	°C	270.1	270
Upper plenum temperature	°C	322.9	325
Maximum core outlet temperature	°C	424.6	430.7
Primary flow rate	kg/s	13829	13800
Core flow rate	kg/s	7716	7711
Secondary water pressure	bar	16	16
Secondary water PHX inlet temperature	°C	198.2	200
Secondary water PHX outlet quality	-	0.30	0.3

- Very good agreement between code-calculated values and design values
  - Limited differences due to different LBE physical properties (mainly  $C_p$ )
- Maximum clad temperature  $\sim 470$  °C
- Maximum fuel temperature  $\sim 1600$  °C (low value due to low linear power  $\sim 110$  W/cm)



# MYRRHA safety analysis: SCS depressurization transient

---

- Unbalance between power delivered by PHXs and removed by aero-condensers → SCS depressurization (16 bar → 1 bar and below)
- Overcooling transient:
  - 4 (out of 4) tertiary fans accidentally restarting at full speed with DH power level in the core
  - SCS depressurization
  - SCS feedwater pumps active
- Transient evaluation performed with RELAP5-3D and RELAP5/Mod3.3



# MYRRHA safety analysis: SCS depressurization transient

- Different transient evolution evaluation by the two codes:
  - Above 5 bar: ~same evaluation
  - Below 5 bar:
    - Nearly no differences in pressure evolution
    - Diverging liquid and vapor temperatures



# MYRRHA safety analysis: SCS depressurization transient

- Minor edit "sattemp" and "tsatt" plotted (supposed to coincide if no non-condensable species present) for both codes:




- Different trends for "sattemp" and "tsatt"
- "tsatt" provides same profile as vapor phase
- "sattemp" lower than the liquid phase
- "sattemp" and "tsatt" profiles match
- "sattemp" and "tsatt" profiles ~equal to vapor phase
- Liquid phase lower than saturation temperature



# MYRRHA safety analysis: SCS depressurization transient

- SCS temperature evolution important towards primary PbBi coolant freezing risk:









- RELAP5-3D and RELAP5/Mod3.3 predicts LBE freezing time of ~1600 s and ~800 s respectively. This difference can have a certain impact for the safety case.

## Experimental validation at low pressures: Zeitoun and Choukri

---

- Preliminary review of available benchmarks: Zeitoun and Choukri experiment:
  - Void generation in heated channel
  - Sensitivity parameters:
    - Pressure (1.07 bar - 1.56 bar)
    - Heat flux and mass flow rate ( $q/m$ : 0.867 kJ/kg – 2.64 kJ/kg)
    - Inlet subcooling temperature (11.4 °C – 23.5 °C)
- Experiments included in RELAP5/Mod3.3 Validation matrix (volume 3) but not in RELAP5-3D developmental assessment documents (volume 3)

# Experimental validation at low pressures: Zeitoun and Choukri



## Experimental validation at low pressures: Zeitoun and Choukri

---







- RELAP5-3D predictions underestimated, especially for high  $q/m$
- RELAP5-3D void fraction estimation quite less sensitive to experiments condition: void fraction prediction very limitedly affected by experimental boundary conditions
- Approaching the experimental channel top, RELAP5-3D predictions often present a maximum in the void fraction function (void fraction decreasing while channel is still heated)
- Other parameters such as wall temperature and water outlet temperature are in acceptable agreement
- Possible reason:
  - RELAP5-3D two-phase SNB model based on former RELAP5/Mod3.2 model (mainly based on high pressure subcooled boiling data)

## Experimental validation at low pressures: THTL

---

- Different experiment: Thermal-Hydraulic Test Loop
  - Void generation in heated channel
  - Experimental conditions:
    - Coolant: light water, upward flow
    - Inlet coolant temperature: 45°C
    - Outlet pressure: 1.7 MPa
    - Local heat flux range: 0.7–18 MW/m<sup>2</sup>
    - Corresponding exit velocity range: 2.8–28.4 m/s

# Experimental validation at low pressures: THTL



## Experimental validation at low pressures: THTL

---

- Difference with respect to experimental data increases with applied heat flux
  - Above 8 MW/m<sup>2</sup>: code simulation crashes with Onset of Flow Instability
  - This behavior is common for both RELAP5-3D and RELAP5/Mod3.3 codes
- At higher pressure (similar to MYRRHA SCS normal operating conditions) there is no observed divergence between the two codes
- Void fraction plotted in function of mass flow rate shows also a good agreement between the two codes
  - Some disturbances only arising when operating at higher heat fluxes
- Two codes found in good agreement at a pressure of ~17 bar (~MYRRHA SCS operation)

- Several transients studied for MYRRHA reactor pre-licensing involve the depressurization of the Secondary Cooling System (SCS), cooled by low pressure two-phase water mixture
- RELAP5-3D overestimates, with respect to RELAP5/Mod3.3, the freezing time ( $\sim 1600$  s vs.  $\sim 800$  s), with potential consequences on the LBE freezing conservative predictions. This is caused by the SCS temperature prediction between the two codes
- The code benchmarking for low pressure showed some shortcomings and limitations of RELAP5-3D subcooled model at low pressures
- Predictions of the two codes are found to be in good agreement with experiments at pressures above  $\sim 10$  bar. In particular, experimental evidence proves the correct behavior at 17 bar.



**Copyright © 2016 - SCK•CEN**

PLEASE NOTE!

This presentation contains data, information and formats for dedicated use ONLY and may not be copied, distributed or cited without the explicit permission of the SCK•CEN. If this has been obtained, please reference it as a “personal communication. By courtesy of SCK•CEN”.

**SCK•CEN**

Studiecentrum voor Kernenergie  
Centre d'Etude de l'Energie Nucléaire  
Belgian Nuclear Research Centre

Stichting van Openbaar Nut  
Fondation d'Utilité Publique  
Foundation of Public Utility

Registered Office: Avenue Herrmann-Debrouxlaan 40 – BE-1160 BRUSSELS  
Operational Office: Boeretang 200 – BE-2400 MOL



STUDIECENTRUM VOOR KERNENERGIE  
CENTRE D'ETUDE DE L'ENERGIE NUCLEAIRE